





NOTE:

- Material: N0-PA66 94V-0
- Welding Board Angle: Blank-ordinary
- Plug the Pin & special No. L- With Lock
- HF-Halogen free

Poles	Dimensions(mm)			Poles	Dimensions(mm)		
	A	B	C		A	B	C
02	1.25	7.65	2.70	11	12.50	18.90	13.95
03	2.50	8.90	3.95	12	13.75	20.15	15.20
04	3.75	10.15	5.20	13	15.00	21.40	16.45
05	5.00	11.40	6.45	14	16.25	22.65	17.70
06	6.25	12.65	7.70	15	17.50	23.90	18.95
07	7.50	13.90	8.95	16	18.75	25.15	20.20
08	8.75	15.15	10.20	20	23.75	30.15	25.20
09	10.00	16.40	11.45	25	30.00	36.40	31.45
10	11.25	17.65	12.70	30	36.25	42.65	37.70

一般公差:GENERAL TOLERANCE		更改說明:REV.DESCRPTION		更改說明:REV.DESCRPTION	
尺寸範圍DIM		△		△	
10.01以上之尺寸	±0.30	△		△	
10.00以內之尺寸	±0.20	△		△	
孔位	±0.10	核准	APPD	模型:	料號: ITEM NO
文件編號		審核	CHD	MODEL	A12542H-00-NP
SC-EW-11		繪圖	DWN	LIAOZTING	2009-3-27
比例: SCALE	SHIH CHUAN ELECTRONICS			規格: SPEC 1.25mm Crimp Style Connectors	

	1	2	3	4																																																																														
A				<table border="1"> <tr> <th>版本REV</th> <th>繪制日期</th> </tr> <tr> <td>A</td> <td>2009-3-27</td> </tr> </table>	版本REV	繪制日期	A	2009-3-27																																																																										
版本REV	繪制日期																																																																																	
A	2009-3-27																																																																																	
B																																																																																		
C																																																																																		
D																																																																																		
E	<p>NOTE:</p> <ul style="list-style-type: none"> • Welding Board Angle Blank—ordinary • Plug the Pin & special No.A—Ultra—thin buckles • Material:LP—LCP 94V—0 ; N0—PA66 94V—0 • HF—Halogen free 		<table border="1"> <thead> <tr> <th rowspan="2">Poles</th> <th colspan="3">Dimensions(mm)</th> <th rowspan="2">Poles</th> <th colspan="3">Dimensions(mm)</th> </tr> <tr> <th>A</th> <th>B</th> <th>C</th> <th>A</th> <th>B</th> <th>C</th> </tr> </thead> <tbody> <tr><td>02</td><td>1.25</td><td>6.10</td><td>4.10</td><td>10</td><td>11.25</td><td>16.10</td><td>14.10</td></tr> <tr><td>03</td><td>2.50</td><td>7.35</td><td>5.35</td><td>11</td><td>12.50</td><td>17.35</td><td>15.35</td></tr> <tr><td>04</td><td>3.75</td><td>8.60</td><td>6.60</td><td>12</td><td>13.75</td><td>18.60</td><td>16.60</td></tr> <tr><td>05</td><td>5.00</td><td>9.85</td><td>7.85</td><td>14</td><td>16.25</td><td>19.85</td><td>17.85</td></tr> <tr><td>06</td><td>6.25</td><td>11.10</td><td>9.10</td><td>15</td><td>17.50</td><td>21.10</td><td>19.10</td></tr> <tr><td>07</td><td>7.50</td><td>12.35</td><td>10.35</td><td>20</td><td>23.75</td><td>27.35</td><td>25.35</td></tr> <tr><td>08</td><td>8.75</td><td>13.60</td><td>11.60</td><td>30</td><td>36.25</td><td>39.85</td><td>37.85</td></tr> <tr><td>09</td><td>10.00</td><td>14.85</td><td>12.85</td><td></td><td></td><td></td><td></td></tr> </tbody> </table>		Poles	Dimensions(mm)			Poles	Dimensions(mm)			A	B	C	A	B	C	02	1.25	6.10	4.10	10	11.25	16.10	14.10	03	2.50	7.35	5.35	11	12.50	17.35	15.35	04	3.75	8.60	6.60	12	13.75	18.60	16.60	05	5.00	9.85	7.85	14	16.25	19.85	17.85	06	6.25	11.10	9.10	15	17.50	21.10	19.10	07	7.50	12.35	10.35	20	23.75	27.35	25.35	08	8.75	13.60	11.60	30	36.25	39.85	37.85	09	10.00	14.85	12.85				
Poles	Dimensions(mm)			Poles		Dimensions(mm)																																																																												
	A	B	C		A	B	C																																																																											
02	1.25	6.10	4.10	10	11.25	16.10	14.10																																																																											
03	2.50	7.35	5.35	11	12.50	17.35	15.35																																																																											
04	3.75	8.60	6.60	12	13.75	18.60	16.60																																																																											
05	5.00	9.85	7.85	14	16.25	19.85	17.85																																																																											
06	6.25	11.10	9.10	15	17.50	21.10	19.10																																																																											
07	7.50	12.35	10.35	20	23.75	27.35	25.35																																																																											
08	8.75	13.60	11.60	30	36.25	39.85	37.85																																																																											
09	10.00	14.85	12.85																																																																															
	一般公差:GENERAL TOLERANCE		更改說明:REV.DESCRPTION																																																																															
	尺寸範圍DIM		更改說明:REV.DESCRPTION																																																																															
	10.01以上之尺寸	±0.30	更改說明:REV.DESCRPTION																																																																															
	10.00以內之尺寸	±0.20	更改說明:REV.DESCRPTION																																																																															
	孔位	±0.10	核准APPD	模型: MODEL																																																																														
	文件編號	SC-EW-11	審核CHD	料號: ITEM NO																																																																														
			繪圖DWN	A12544H-00-NP																																																																														
			LIAOZTING	2009-3-27																																																																														
	比例: SCALE			規格: SPEC																																																																														
				1.25mm Crimp Style Connectors																																																																														